




Safe AS-Interface ClassicLine module with quick mounting technology

ClassicL 2SI 2DOT 2LO OSSD



Application

Design	housing for DIN rail mounting
Application	AS-i Safety at Work

Electrical data

Operating voltage	[V]	26.5...31.6 DC; (cULus - Class 2 source required)
Max. current consumption from AS-i	[mA]	280
Protection class		III
Reverse polarity protection		yes; (AS-i)
Reverse polarity protection		yes
Max. current load per module/slot	[A]	0.2
Integrated watchdog		yes

Inputs / outputs

Number of inputs and outputs	Number of digital inputs: 2; Number of digital outputs: 2
------------------------------	---

Inputs

Number of digital inputs		2; (2 x safety input)
Input circuit of digital inputs		PNP
Sensor supply of the inputs		AS-i
Voltage supply	[V]	19.2...30
Max. total current rating of inputs	[mA]	200
Input current limitation	[mA]	8
Input current High	[mA]	> 6
Input current low	[mA]	< 2



Safe AS-Interface ClassicLine module with quick mounting technology

ClassicL 2SI 2DOT 2LO OSSD

Switching level high	[V]	> 11
Switching level low	[V]	< 5
Overload protection digital inputs		yes
Short-circuit detection		yes
Cross-fault monitoring		no
Short-circuit proof		yes

Outputs

Output signal		switching signal
Number of digital outputs		2
Voltage range DC	[V]	18...28.8; (AS-i)
Max. current load per output	[mA]	50
Short-circuit protection		yes
Short-circuit proof		yes
Overload protection		yes
Electrically separated		no
Actuator supply outputs		AS-i

Operating conditions

Ambient temperature	[°C]	-25...55
Note on ambient temperature		with switched outputs: -25...40 °C
Max. relative air humidity	[%]	95
Max. height above sea level	[m]	2000
Protection		IP 67
Pollution degree		2

Tests / approvals

EMC	EN 62026-2	
	EN 61326-3-1	
Shock resistance	EN 60068-2-27	
Vibration resistance	EN 60068-2-6	

Safety classification

Complies with the requirements		ISO 13849-1 Category 4, PL e
		IEC 61508 SIL 3
Mission time TM (additional indication)		20 years
PFH	[1/h]	2,33E-11

AS-i classification

AS-i version		2.11; 3.0
AS-i addressing		Addressing socket
Extended addressing mode		no
AS-i master profile		M3; M4
AS-i profile		S-7.B.E
AS-i I/O configuration	[hex]	7
AS-i ID code	[hex]	B.E
AS-i certificate		126301

AC507S



Safe AS-Interface ClassicLine module with quick mounting technology

ClassicL 2SI 2DOT 2LO OSSD

Data bits	Data bit assignment	D0	D1	D2	D3
		O1	O2	O3	O4

Mechanical data	
Weight	[g] 294.5
Housing	rectangular
Type of mounting	AS-i flat cable connection; Mounting on DIN rail; (TH35 (EN 60715))
Dimensions	[mm] 103 x 45 x 44.7
Material	housing: PA; Piercing contacts: CuSn6 nickel-plated and tin-plated

Displays / operating elements		
Display	Power	1 x LED, green
	errors	1 x LED, red
	Switching status	1 x LED, yellow
	alarm	1 x LED, red


Electrical connection	
Module connection	Flat cable
Accessories	
Items supplied	lower part
Accessories (optional)	Addressing cable:, E70213
	Protective cap: M12, E73004

Remarks	
Remarks	PL e, cat. 4, SIL 3 only if the fault exclusions described in the manual are used
Pack quantity	1 pcs.

Electrical connection	
quick mounting technology for AS-i flat cable: ; three selectable directions	

Electrical connection - O-3/4


Connector: 1 x M12; coding: A; Contacts: 3; Maximum cable length: 10 m



1	n.c.	
2		O-4
3 (I-)	L-	
4		O-3
5	n.c.	

Electrical connection - O-4

Connector: 1 x M12; coding: A; Contacts: 2; Maximum cable length: 10 m



1	n.c.	
2	n.c.	
3 (I-)	L-	
4		O-4
5	n.c.	




Safe AS-Interface ClassicLine module with quick mounting technology

ClassicL 2SI 2DOT 2LO OSSD

Electrical connection - SI-1/2


Connector: 1 x M12; coding: A; Contacts: 5; Maximum cable length: 10 m



1 (I+)	L+	
2		SI-2
3 (I-)	L-	
4		SI-1
5		FE

Electrical connection - Trans

Connector: 1 x M12; coding: A; Contacts: 5; Maximum cable length: 10 m



1 (I+)	L+	
2 (I-)	L-	
3 (I-)	L-	
4 (I+)	L+	
5		FE

FE: functional earth; n.c.: not used