




AS-Interface ClassicLine module with quick mounting technology

ClassicLine 3DO-Y IP67



Application	
Design	housing for DIN rail mounting
Application	field installation
Electrical data	
Operating voltage [V]	26.5...31.6 DC; (cULus - Class 2 source required)
Max. current consumption from AS-i [mA]	50
Additional voltage supply [V]	15...30 DC; (AUX)
Max. current consumption from additional supply [mA]	3000
Integrated watchdog	yes
Inputs / outputs	
Number of inputs and outputs	Number of digital outputs: 3
Outputs	
Number of digital outputs	3
Circuit	PNP
Voltage range DC [V]	15...30; (to PELV; via flat cable)
Max. current load per output [mA]	1000; (utilization category DC-13 (control of electromagnets): 20 W (IEC 60947-5-1))
Max. current load outputs total [A]	3
Short-circuit proof	yes
Electrically separated	yes
Actuator supply outputs	AUX



AS-Interface ClassicLine module with quick mounting technology

ClassicLine 3DO-Y IP67

Operating conditions					
Ambient temperature	[°C]	-25...70			
Protection		IP 67			
Tests / approvals					
EMC		EN 50295			
		IEC 61000-6-2			
MTTF	[years]	215			
AS-i classification					
AS-i version		2.11; 3.0			
AS-i addressing		Addressing socket			
Extended addressing mode		yes			
AS-i master profile		M2; M3; M4			
AS-i profile		S-8.A.E			
AS-i I/O configuration	[hex]	8			
AS-i ID code	[hex]	A.E			
Data bits	Data bit	D0	D1	D2	D3
	Output	1	2	3	-
	Socket	O-1/2	O-1/2 O-2	O-3	-
	Pin	4	2 4	4	-
Mechanical data					
Weight	[g]	155.1			
Housing		rectangular			
Type of mounting		AS-i flat cable connection; Mounting on DIN rail; (TH35 (EN 60715))			
Dimensions	[mm]	103 x 45 x 44.7			
Material		PA; Piercing contacts: CuSn6 nickel-plated and tin-plated			
Displays / operating elements					
Display	Power			LED, green	
	errors			LED, red	
	Function			LED, yellow	
Electrical connection					
Module connection		Flat cable			
Accessories					
Items supplied		lower part			
Accessories (optional)		Protective cap: M12, E73004			
Remarks					
Pack quantity		1 pcs.			




AS-Interface ClassicLine module with quick mounting technology

ClassicLine 3DO-Y IP67

Electrical connection

quick mounting technology for AS-i flat cable: ; three selectable directions

Connection



Connector: M12

	Outputs
	Socket O-1/2
1	not used
2	Switching output 2
3	External voltage AUX -
4	Switching output 1
5	not used
	Socket O-2
1	not used
2	not used
3	External voltage AUX -
4	Switching output 2
5	not used
	Socket O-3
1	not used
2	not used
3	External voltage AUX -
4	Switching output 3
5	not used