


AL5228



IO-Link AirBox with quick mounting technology

IOL AirBox 2x3/2 4x2DI



IO-Link



Product characteristics

Number of inputs and outputs Number of digital inputs: 8; Number of pneumatic outputs: 2

Application

Design	housing for DIN rail mounting
Application	field installation; for use in wet environments
Media	compressed air
Medium temperature [°C]	-10...50

Electrical data

Operating voltage [V]	18...30 DC; (to SELV/PELV)
Nominal voltage DC [V]	24
Current consumption [mA]	80...680; (24 V DC, full load)
Overvoltage category	II

Inputs / outputs

Number of inputs and outputs Number of digital inputs: 8; Number of pneumatic outputs: 2

Inputs

Number of digital inputs	8; (4 x 2)
Input circuit of digital inputs	PNP



IO-Link AirBox with quick mounting technology

IOL AirBox 2x3/2 4x2DI

Sensor supply of the inputs	US		
Voltage supply [V]	18...30; (from the operating voltage)		
Max. total current rating of inputs [mA]	400		
Input current High [mA]	2...3.5		
Input current low [mA]	0...1.5		
Switching level high [V]	> 11		
Digital inputs protected against short circuits	yes		
Outputs			
Number of pneumatic outputs	2		
Actuator supply outputs	US		
Interfaces			
Communication interface	IO-Link		
Transmission type	COM2 (38,4 kBaud)		
IO-Link revision	1.1		
SDCI standard	IEC 61131-9		
Profiles	Common - I&D	Identification and Diagnosis	
	Function	Locator	
	Function	ProductURI	
SIO mode	no		
Required master port class	A		
Min. process cycle time [ms]	2.7		
Supported DeviceIDs	Type of operation	DeviceID	
	default	1503	
Operating conditions			
Ambient temperature [°C]	-10...55		
Note on ambient temperature	Switching frequency < 1,66 Hz: -10...50 °C		
	Switching frequency > 1,66 Hz: -10...55 °C		
Max. relative air humidity [%]	90; (non condensing)		
Max. height above sea level [m]	4000		
Protection	IP 65; IP 67		
Pollution degree	2		
Mechanical data			
Weight [g]	311		
Housing	rectangular		
Type of mounting	Mounting on DIN rail; quick mounting; AS-i flat cable connection; (TH35 (EN 60715))		
Dimensions [mm]	109 x 85 x 52		
Material	housing: PA 6.6; AirBox housing: PA 6; sealing: TPE; sealing rings: NBR		
Pneumatic system	2 x 3/2-way slide valves (free from overlapping)		
Operating pressure range	2...8 bar	0.2...0.8 MPa	29...116 psi
Air flow at 6/5 bar [l/min]	500		
Permissible compressed air	non-lubricated compressed air class 6-3-1; lubricated compressed air class 6-3-4		
Manual override	pressing/releasing or pressing/turning/locking		
Tube fittings	8 mm		

AL5228



IO-Link AirBox with quick mounting technology

IOL AirBox 2x3/2 4x2DI

Exhaust	exhaust can be discharged through tube connection
---------	---

Displays / operating elements

Display	Power	LED, green
	errors	LED, red
	Function	LED, yellow

Accessories


Items supplied	lower part
Accessories (optional)	Mounting plate:, E74999
	Module lower part:, E75000
	Protective cap: M12, E73004
	sealing plug:, E75231
	Silencer:, E75232
	Push-in L-fitting:, E75228
	Push-in T-fitting:, E75227

Remarks

Remarks	If not pneumatically operated, E75231 sealing plug must be inserted.
	Avoid ingress of dirt and dust.
	Do not connect any of the following points to an external potential:
	L-, L+, I-1, I-2, I-3, I-4
	Please see the notes on compressed air and EMC/ESD under "Downloads"
Pack quantity	1 pcs.

Electrical connection - Socket

Connector: 4 x M12; coding: A; Contacts: 5



Digital input X1.0...X1.3

1	L+
2	IN2 DI2
3	L-
4	IN1 DI1
5	n.c.

Electrical connection - plug

Connector: 1 x M12; coding: A; Contacts: 4



voltage supply X1

1	L+
2	n.c.
3	L-
4	IO-Link

AL5228




IO-Link AirBox with quick mounting technology

IOL AirBox 2x3/2 4x2DI

Diagrams and graphs

Pneumatic symbol



2 x 3/2-way slide valves (free from overlapping)