


DS2505



Evaluation unit for slip and synchronous monitoring

MONITOR/FS-2 /110-240VAC/DC



- 1 OLED display
- 2 Programming buttons
- 3 LEDs



Product characteristics

Housing	rectangular
Dimensions [mm]	78 x 45 x 124.7

Application

Design	housing for DIN rail mounting
Application	pulse evaluation system with microprocessor for slip and synchronous monitoring; evaluation of pulse differences

Electrical data

Nominal voltage AC [V]	110...240
Nominal voltage DC [V]	27
Nominal voltage tolerance [%]	< 10
Nominal voltage tolerance 2 [%]	20...10
Nominal frequency AC [Hz]	50...60
Power consumption [W]	3
Auxiliary energy for sensors DC [V]	19.6...27.7; (SELV, ≤ 150 mA)

Inputs / outputs

Number of inputs and outputs	Number of relay outputs: 2
------------------------------	----------------------------

Outputs

Number of relay outputs	2
Contact rating	6 A (250 V AC, 30 V DC); B300, R300; (resistive load)

Measuring/setting range

Measuring range [Hz]	0.1...400
----------------------	-----------

Operating conditions

Ambient temperature [°C]	-40...60
Storage temperature [°C]	-40...85
Max. relative air humidity [%]	80; (40 °C: 50 %)



Evaluation unit for slip and synchronous monitoring

MONITOR/FS-2 /110-240VAC/DC

Protection	IP 50
Protection rating terminals	IP 20
Pollution degree	2

Tests / approvals

EMC	EN 61010	2011
	EMV 89/336/EWG	
	EN 61000-6-2	2005
	EN 61000-6-4	2007

Mechanical data

Weight	[g]	373.95
Housing		rectangular
Type of mounting		Mounting on DIN rail; (TH35 (EN 60715))
Dimensions	[mm]	78 x 45 x 124.7
Material		housing: plastics

Displays / operating elements

Display		OLED display, 128 x 64 pixels luminous
	Switching status	LED, green

Remarks

Remarks	the device complies with overvoltage category II
Pack quantity	1 pcs.

Electrical connection

dual-chamber terminals: 2 x ...2.5 mm²; AWG 14

1	DC Supply voltage (L-)
2	DC Supply voltage (L+)
3	Supply transistor outputs (L+)
4	sensor signal 1 pnp
5	DC Sensor supply (L+)
6	DC Sensor supply (L-)
7	AC Supply voltage (L)
8	AC Supply voltage (N)
9	not used
10	sensor signal 1 npn
11	sensor signal 2 pnp
12	sensor signal 2 npn
13	Relay 1 common
14	Relay 1 normally open
15	Relay 1 normally closed
16	transistor output 1 pnp
17	release 1/2 pnp
18	Reset 1/2 pnp
19	Relay 2 common
20	Relay 2 normally open
21	Relay 2 normally closed
22	not used
23	not used
24	transistor output 2 pnp