


E2M200



Adapter cables for cameras with video output

ADAPTER CABLE M12-M16



Application	
Special feature	Free from silicone; gold-plated contacts
Design	camera with video output O2M20x
Application	Use in mobile and harsh applications
Free from silicone	yes

Electrical data	
Operating voltage [V]	< 60 DC
Protection class	II
Max. current load total [A]	4

Operating conditions	
Ambient temperature [°C]	-45...85
Protection	IP 67

Mechanical data	
Weight [g]	72.2
Mounting thread	M16
Material	housing: PVC; sealing: EPDM
Material nut	PVC


Remarks	
Pack quantity	1 pcs.

Electrical connection	
Cable: 0.6 m, PVC, black, Ø 6 mm; 3 x 0.34 mm ² / AWG 22 + 1 x 0.11 mm ² / AWG 26	

Electrical connection - Socket	
Connector: 1 x M16, straight; coding: A; Contacts: 4, gold-plated; Locking: PVC; Tightening torque: 0.6...1.5 Nm	



Electrical connection - plug	
Connector: 1 x M12, straight; coding: A; Contacts: 5, gold-plated; Locking: PVC; Tightening torque: 0.6...1.5 Nm	




E2M200



Adapter cables for cameras with video output

ADAPTER CABLE M12-M16

Connection



BK =
GY =
RD =

Core colors :
black
grey
red