


E3R114



Connection cable

HF FAKRA CABLE 1x S/S/M S/S/F A DRAG 10M



Application		
Special feature	Drag chain suitability	
Application	Industrial applications	
Oil resistant	yes	
Electrical data		
Operating voltage	[V]	< 50 AC / < 60 DC
Protection class	III	
Damping	[dB/m]	1.6
Internal resistance (Ri)	[Ω]	50; (± 3 Ω)
Operating conditions		
Ambient temperature	[°C]	-10...60
Ambient temperature (moving)	[°C]	-10...60
Protection	IP 54	
Mechanical data		
Weight	[g]	522
Material	Cable: PUR black	
Drag chain suitability	yes	
Drag chain suitability	Bending radius for flexible applications	85
	Bending radius for fixed installation	60
	Bending radius	80
	Bending cycles	2.000.000
	Travel speed	max. 4 m/s at 4 m horizontal travel length and max. acceleration of 8 m/s²
Fixed installation		
Min. bending radius	[mm]	19.8
Loose installation		
Min. bending radius	[mm]	56
Accessories		
Accessory required	Adapter cable, E3R108	
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Connector: 1 x HF-Single, straight		
Electrical connection		
Cable: 10 m, black, Ø 5.6 mm		