




Welding adapters EN10357 series C (ASME BPE)

ADAPT EN10357-C DN100



EC 1935/2004

FCM



Hygienic
Cleanable

Application

Design

for flow meter SMF

Application

food and beverage industry; hygienic systems

Pressure rating

25 bar

2.5 MPa

Tests / approvals

Pressure equipment directive

A possible classification to PED depends on the application and has to be carried out by the user / operator.

Safety instructions

The compatibility between medium and product material has to be checked in all applications.



Welding adapters EN10357 series C (ASME BPE)

ADAPT EN10357-C DN100

Mechanical data		
Weight	[g]	4815.5
Housing		tubular
Dimensions	[mm]	Ø 168 / L = 42.9
Materials (wetted parts)		stainless steel (1.4404 / 316L)
Nominal diameter		DN100 (4")
Sensor connection		ifm-specific device flange
Process connection		Welding adapter EN10357 series C (ASME BPE)
Process connection suitable for pipe standard		(DIN EN 10357 series C); (DIN EN 10357 series D); (DIN 11866 series C); (BS 4825 Part 1); (ISO 2037)
Surface characteristics Ra/Rz of the wetted parts		Ra < 0.4 µm
Accessories		
Items supplied		screws 12
Remarks		
Pack quantity		2 pcs.