




Welding adapters EN10357 series D (SMS)

ADAPT EN10357-D DN40



EC 1935/2004

FCM



Hygienic
Cleanable

Application

Design	for flow meter SMF	
Application	food and beverage industry; hygienic systems	
Pressure rating	40 bar	4 MPa
MAWP (for applications according to CRN) [MPa]	4	

Tests / approvals

Pressure equipment directive	A possible classification to PED depends on the application and has to be carried out by the user / operator.
Safety instructions	The compatibility between medium and product material has to be checked in all applications.

Mechanical data

Weight [g]	2361.7
Housing	tubular

E40632



Welding adapters EN10357 series D (SMS)

ADAPT EN10357-D DN40

Dimensions	[mm]	Ø 99 / L = 42.9
Materials (wetted parts)		stainless steel (1.4404 / 316L)
Nominal diameter		DN40 (1 1/2")
Sensor connection		ifm-specific device flange
Process connection		Welding adapter EN10357 series D (SMS); ISO 2037
Process connection suitable for pipe standard		(ISO 2037); (JIS G3447); (DIN EN 10357 series D)
Surface characteristics Ra/Rz of the wetted parts		Ra < 0.4 µm
Accessories		
Items supplied		screws 8
Remarks		
Remarks		
Pack quantity		2 pcs.