




Wiring block

ZDO4H050MSS0000-00STAK120MSS



Application		
Special feature		Free from silicone; gold-plated contacts
Application		Industrial applications; Oils and coolants
Free from silicone		yes
Electrical data		
Operating voltage	[V]	< 30 DC; (cULus - Class 2 source required)
Max. current load per module/slot	[A]	4
Max. current load total	[A]	12
Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67
Tests / approvals		
UL approval	Enclosure type	Type 1
Mechanical data		
Weight	[g]	236.5
Housing		rectangular



Wiring block

ZDO4H050MSS0000-00STAK120MSS

Type of mounting	Backplane mounting
Dimensions [mm]	118.2 x 60 x 33
Material	housing: PA
Number of ports splitter box	4
Connector type	M12

Accessories


Items supplied	Protective caps: 2 labels: 4
----------------	---------------------------------

Remarks


Pack quantity	1 pcs.
---------------	--------

Electrical connection - Connection

Connector: 1 x M23; Contacts: 12, gold-plated; Tightening torque: 0.8...1.5 Nm



Connection



Electrical connection - slot

Connector: 4 x M12; coding: A; Contacts: 4, gold-plated; Tightening torque: 0.8...1.5 Nm

