




Wiring block

ZDO4F035MSJ0000---STGH080MSJ



Application

Special feature	gold-plated contacts
Application	Industrial applications; Oils and coolants

Electrical data

Operating voltage	[V]	10...30 DC; (cULus - Class 2 source required)
Protection class		III
Max. current load per module/slot	[A]	2
Max. current load total	[A]	2

Outputs

Electrical design	NPN
-------------------	-----

Operating conditions

Ambient temperature	[°C]	-25...80
Ambient temperature (moving)	[°C]	-5...60
Protection		IP 65; IP 67; IP 68; (1 m / 7 days)

Mechanical data


Weight	[g]	88
Housing		rectangular
Type of mounting		Backplane mounting
Dimensions	[mm]	85.4 x 30 x 23.7
Material		housing: PBT-GF20
Material nut		brass, nickel-plated
Number of ports splitter box		4
Connector type		M8




Wiring block

ZDO4F035MSJ0000---STGH080MSJ

Displays / operating elements		
Display	Switching status	4 x LED, yellow
	Power	1 x LED, green
Accessories		
Accessories (optional)	DIN rail adapter:, E73006	
	Protective cap: M8, E73005	
Remarks		
Pack quantity	1 pcs.	

Electrical connection - Connection	
Connector: 1 x M12; coding: A; Contacts: 8, gold-plated; Locking: brass, nickel-plated	
	



Electrical connection - slot	
Connector: 4 x M8; coding: A; Contacts: 3, gold-plated; Locking: brass, nickel-plated	
	