




Wirable plug set for mobile controllers


BasicContact-Set/for CR0421

①




0,5...1,5 mm²

②




0,5...1,5 mm²




1,0...2,5 mm²

③




1,0...2,5 mm²

④




0,5...1,5 mm²




2,0...3,0 mm²

⑤



M6 (10 mm²)



M8 (10 mm²)

1

spade sockets 2.8 x 0.8 mm

2

spade sockets 6.3 x 0.8 mm

3

spade sockets 6.3 x 0.8 mm fully insulated

4

Contacts for automotive fuse holders

5

Ring terminals

Application		
Design		for BasicRelay, utilizing all connections to a BasicRelay, CR0421
Application		Industrial applications; Use in mobile and harsh applications
Mechanical data		
Weight	[g]	85.5
Dimensions	[mm]	134.5 x 50.6 x 210



Wirable plug set for mobile controllers

BasicContact-Set/for CR0421

Accessories

Items supplied

blade female terminals for relay contacts: 10 x (2,8 x 0,8 mm (0,5...1,0 mm ²)), DIN 46340
blade female terminals for relay contacts: 20 x (6,3 x 0,8 mm (0,5...1,0 mm ²)), DIN 46340
blade female terminals for relay contacts: 20 x (6,3 x 0,8 mm (1,0...2,5 mm ²)), DIN 46340
blade female terminals for power distributors: 20 x (6,3 x 0,8 mm (1,0...2,5 mm ²)), fully insulated DIN 46245
Contacts for automotive fuse holders: 6 x (0,5...1,5 mm ²)
Contacts for automotive fuse holders: 4 x (2,0...3,0 mm ²)
ring terminals for power supply: 1 x M6 (10 mm ²), DIN 46234
ring terminals for power supply: 1 x M8 (10 mm ²), DIN 46234
Nuts: 1 x M6, galvanized ISO 4032
Nuts: 1 x M8, galvanized ISO 4032

Electrical connection

terminals: