


# EVC166



## Female cordset

ADOAH020MSS0010H02



### Application

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Special feature    | Free from silicone; Halogen-free; gold-plated contacts; Drag chain suitability |
| Application        | Industrial applications; Oils and coolants                                     |
| Free from silicone | yes                                                                            |

### Electrical data

|                         |     |                     |
|-------------------------|-----|---------------------|
| Operating voltage       | [V] | < 250 AC / < 300 DC |
| Protection class        |     | II                  |
| Max. current load total | [A] | 4                   |

### Operating conditions

|                                                                 |      |                             |
|-----------------------------------------------------------------|------|-----------------------------|
| Ambient temperature                                             | [°C] | -25...90                    |
| Note on ambient temperature                                     |      | cULus: ...75                |
| Ambient temperature (moving)                                    | [°C] | -25...90                    |
| Note on ambient temperature (moving)                            |      | cULus: ...75                |
| Storage temperature                                             | [°C] | -25...55                    |
| Storage humidity                                                | [%]  | 10...100                    |
| Other climatic conditions for storage according to stated class |      | 1K22/ DIN 60721-3-1         |
| Protection                                                      |      | IP 65; IP 67; IP 68; IP 69K |

### Mechanical data

|                        |                                          |                                                                                                |
|------------------------|------------------------------------------|------------------------------------------------------------------------------------------------|
| Weight                 | [g]                                      | 300.5                                                                                          |
| Dimensions             | [mm]                                     | 26.5 x 15.5 x 36.5                                                                             |
| Molded-body material   |                                          | TPU (urethane)                                                                                 |
| Material nut           |                                          | brass, nickel-plated                                                                           |
| Sealing material       |                                          | FKM                                                                                            |
| Drag chain suitability |                                          | yes                                                                                            |
| Drag chain suitability | Bending radius for flexible applications | min. 10 x cable diameter                                                                       |
|                        | Travel speed                             | max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s <sup>2</sup> |
|                        | Bending cycles                           | > 5 Mio.                                                                                       |
|                        | Torsional strain                         | ± 180 °/m                                                                                      |

### Remarks

|               |        |
|---------------|--------|
| Pack quantity | 1 pcs. |
|---------------|--------|

# EVC166



## Female cordset

ADOAH020MSS0010H02

### Electrical connection

Cable: 10 m, PUR, Halogen-free, black, Ø 4.9 mm; 2 x 0.34 mm<sup>2</sup> (42 x Ø 0.1 mm )

### Electrical connection - Socket

Connector: 1 x M12, angled; coding: A; Contacts: 2, gold-plated; Moulded body: TPU (urethane), orange; Locking: brass, nickel-plated; sealing: FKM; Tightening torque: 0.6...1.5 Nm



### Connection

|      |               |   |    |
|------|---------------|---|----|
|      |               | 1 | WH |
|      |               | 4 | BK |
| BK = | Core colors : |   |    |
| WH = | black         |   |    |
|      | white         |   |    |