




## Female cordset

ADOGH040MSS0040H04

Please see the technical note under "Downloads"



## Application

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Special feature    | Free from silicone; Halogen-free; gold-plated contacts; Drag chain suitability |
| Application        | Industrial applications; Oils and coolants                                     |
| Free from silicone | yes                                                                            |

## Electrical data

|                         |     |                     |
|-------------------------|-----|---------------------|
| Operating voltage       | [V] | < 250 AC / < 300 DC |
| Protection class        |     | II                  |
| Max. current load total | [A] | 4                   |

## Operating conditions

|                                                                 |      |                             |
|-----------------------------------------------------------------|------|-----------------------------|
| Ambient temperature                                             | [°C] | -25...90                    |
| Note on ambient temperature                                     |      | cULus: ...75 °C             |
| Ambient temperature (moving)                                    | [°C] | -25...90                    |
| Note on ambient temperature (moving)                            |      | cULus: ...75 °C             |
| Storage temperature                                             | [°C] | -25...55                    |
| Storage humidity                                                | [%]  | 10...100                    |
| Other climatic conditions for storage according to stated class |      | 1K22/ DIN 60721-3-1         |
| Protection                                                      |      | IP 65; IP 67; IP 68; IP 69K |

## Mechanical data

|                        |                                          |                                                                                                |
|------------------------|------------------------------------------|------------------------------------------------------------------------------------------------|
| Weight                 | [g]                                      | 827                                                                                            |
| Dimensions             | [mm]                                     | 15.5 x 15.5 x 45                                                                               |
| Molded-body material   |                                          | TPU (urethane)                                                                                 |
| Material nut           |                                          | brass, nickel-plated                                                                           |
| Sealing material       |                                          | FKM                                                                                            |
| Drag chain suitability |                                          | yes                                                                                            |
| Drag chain suitability | Bending radius for flexible applications | min. 10 x cable diameter                                                                       |
|                        | Travel speed                             | max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s <sup>2</sup> |
|                        | Bending cycles                           | > 5 Mio.                                                                                       |
|                        | Torsional strain                         | ± 180 °/m                                                                                      |

## Remarks

|       |                                                 |
|-------|-------------------------------------------------|
| Notes | Please see the technical note under "Downloads" |
|-------|-------------------------------------------------|

EVC759



Female cordset

ADOGH040MSS0040H04

Pack quantity


1 pcs.

Electrical connection


Cable: 40 m, PUR, Halogen-free, black, Ø 4.3 mm; 4 x 0.34 mm<sup>2</sup> (42 x Ø 0.1 mm )

Electrical connection - Socket

Connector: 1 x M12, straight; coding: A; Contacts: 4, gold-plated; Moulded body: TPU (urethane), orange; Locking: brass, nickel-plated; sealing: FKM; Tightening torque: 0.6...1.5 Nm



Connection



BK =

BN =

BU =

WH =

Core colors :

black


brown

blue

white

Diagrams and graphs

Characteristic curve for derating



Derating I<sub>max</sub> \* 0.8 (DIN EN 60512-5-2)

X Ambient temperature [°C]

Y Current [A]