


EVC945



All male cordsets


ASTAH050MSD0002C05



Application		
Special feature	Halogen-free; gold-plated contacts; screened cable; Drag chain suitability	
Application	Use in mobile and harsh applications; CAN bus	
Electrical data		
Operating voltage	[V]	< 30 AC / < 36 DC
Max. current load total	[A]	4
Operating conditions		
Ambient temperature	[°C]	-25...80
Protection	IP 67; IP 68; IP 69K	
Mechanical data		
Weight	[g]	214.5
Molded-body material	PUR	
Material nut	brass, nickel-plated	
Drag chain suitability	yes	
Drag chain suitability	Bending radius for flexible applications	min. 10 x cable diameter
	Travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s²
	Bending cycles	> 5 Mio.
	Torsional strain	± 180 °/m
Remarks		
Pack quantity	1 pcs.	

Electrical connection	
Cable: 2 m, PUR, Halogen-free, lilac, Ø 8.4 mm, screened; RD / BK: 2 x 0.75 mm ² (42 x Ø 0.15 mm) + WH / BU: 2 x 0.5 mm ² (19 x Ø 0.19 mm) + screen: 1 x 0.75 mm ² (42 x Ø 0.15 mm)	

Electrical connection - plug	
Connector: 1 x M12, angled; coding: A; Contacts: 5, gold-plated; Moulded body: PUR, black; Locking: brass, nickel-plated; Tightening torque: 0.6...1.5 Nm	




EVC945



All male cordsets

ASTAH050MSD0002C05

Connection



BK = Core colors :
BU = black
RD = blue
WH = red
screen = white
screen