




Inductive sensor

IEBC005-ASKG/0,3M/AS



Product characteristics

Electrical design	PNP/NPN
Output function	normally open
Sensing range [mm]	5
Housing	Threaded type
Dimensions [mm]	M8 x 1 / L = 36

Electrical data

Operating voltage [V]	10...30 DC
Current consumption [mA]	< 10; (only in 3-wire operation)
Protection class	III
Reverse polarity protection	yes

Outputs

Electrical design	PNP/NPN
Output function	normally open
Max. voltage drop switching output DC [V]	2.8
Minimum load current [mA]	2; (only in 2-wire operation)
Max. leakage current [mA]	0.5; (only in 2-wire operation)
Permanent current rating of switching output DC [mA]	100
Switching frequency DC [Hz]	700
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Monitoring range

Sensing range [mm]	5
Real sensing range S_r [mm]	$5 \pm 10 \%$
Operating distance [mm]	0...4.05

Accuracy / deviations

Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminum: 0.4 / copper: 0.3
Hysteresis [% of S_r]	1...15
Switch-point drift [% of S_r]	-10...10

Operating conditions

Ambient temperature [°C]	0...60
--------------------------	--------

IE5346



Inductive sensor

IEBC005-ASKG/0,3M/AS

Protection	IP 65; (with ifm socket duly screwed on: IP 67)
------------	---

Tests / approvals

EMC	EN 60947-5-2	
MTTF [years]		2988
UL approval	Ta	-25...70 °C
	Enclosure type	Type 1
	voltage supply	Limited Voltage/Current
	UL approval number	A056
	File number UL	E174191

Mechanical data

Weight [g]	24.2
Housing	Threaded type
Mounting	non-flush mountable
Dimensions [mm]	M8 x 1 / L = 36
Thread designation	M8 x 1
Material	housing: brass white bronze coated; sensing face: PBT orange; lock nuts: brass
Tightening torque [Nm]	A = 5 mm: 1,5 Nm; B: 2 Nm

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	lock nuts: 2
----------------	--------------


Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection - plug

Cable: 0.3 m, PVC, black, Ø 3.4 mm; 3 x 0.14 mm²

Connector: 1 x M8; coding: A; Contacts: 3; Locking: snap-fit



2-wire PNP

1	L+	
3	n.c.	
4	L-	DO (NO) (PNP)

2-wire NPN

1	L+	DO (NO) (NPN)
3	n.c.	
4	L-	

IE5346



Inductive sensor

IEBC005-ASKG/0,3M/AS

3-wire PNP

1 L+
3 L-
4 OUT DO (NO) (PNP)

DO: digital output; NO: normally open

Diagrams and graphs

Installation

