




Inductive sensor

IGK2005-ABOA/PH



Product characteristics

|                 |      |                  |
|-----------------|------|------------------|
| Output function |      | normally open    |
| Sensing range   | [mm] | 5                |
| Housing         |      | Threaded type    |
| Dimensions      | [mm] | M18 x 1 / L = 55 |

Electrical data

|                             |     |                |
|-----------------------------|-----|----------------|
| Operating voltage           | [V] | 20...250 AC/DC |
| Protection class            |     | II             |
| Reverse polarity protection |     | yes            |

Outputs

|                                                 |      |                                                 |
|-------------------------------------------------|------|-------------------------------------------------|
| Output function                                 |      | normally open                                   |
| Max. voltage drop switching output DC           | [V]  | 6.5                                             |
| Max. voltage drop switching output AC           | [V]  | 6.5                                             |
| Minimum load current                            | [mA] | 5                                               |
| Max. leakage current                            | [mA] | 2.5 (250 V AC) / 1.3 (110 V AC) / 0.8 (24 V DC) |
| Permanent current rating of switching output AC | [mA] | 250; (350 (...50 °C))                           |
| Permanent current rating of switching output DC | [mA] | 100                                             |
| Short-time current rating of switching output   | [mA] | 2200; (20 ms / 0,5 Hz)                          |
| Switching frequency AC                          | [Hz] | 25                                              |
| Switching frequency DC                          | [Hz] | 100                                             |

# IG0378



## Inductive sensor

IGK2005-ABOA/PH

|                               |           |                                                                             |
|-------------------------------|-----------|-----------------------------------------------------------------------------|
| Short-circuit proof           |           | no                                                                          |
| Overload protection           |           | no                                                                          |
| Monitoring range              |           |                                                                             |
| Sensing range                 | [mm]      | 5                                                                           |
| Real sensing range Sr         | [mm]      | 5 ± 10 %                                                                    |
| Operating distance            | [mm]      | 0...4.05                                                                    |
| Accuracy / deviations         |           |                                                                             |
| Correction factor             |           | steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminum: 0.4 / copper: 0.3  |
| Hysteresis                    | [% of Sr] | 1...15                                                                      |
| Switch-point drift            | [% of Sr] | -10...10                                                                    |
| Operating conditions          |           |                                                                             |
| Ambient temperature           | [°C]      | -25...80                                                                    |
| Protection                    |           | IP 67                                                                       |
| Tests / approvals             |           |                                                                             |
| EMC                           |           | EN 60947-5-2                                                                |
| MTTF                          | [years]   | 607                                                                         |
| Mechanical data               |           |                                                                             |
| Weight                        | [g]       | 133.5                                                                       |
| Housing                       |           | Threaded type                                                               |
| Mounting                      |           | flush mountable                                                             |
| Dimensions                    | [mm]      | M18 x 1 / L = 55                                                            |
| Thread designation            |           | M18 x 1                                                                     |
| Material                      |           | housing: brass white bronze coated; sensing face: PBT                       |
| Displays / operating elements |           |                                                                             |
| Display                       |           | Switching status1 x LED, yellow                                             |
| Electrical connection         |           |                                                                             |
| Required protection           |           | miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting                    |
| Accessories                   |           |                                                                             |
| Items supplied                |           | lock nuts: 2                                                                |
| Remarks                       |           |                                                                             |
| Remarks                       |           | Recommendation: check the unit for reliable function after a short circuit. |
| Pack quantity                 |           | 1 pcs.                                                                      |

# IG0378




## Inductive sensor

IGK2005-ABOA/PH

### Electrical connection

Cable: 2 m, PPU; 2 x 0.5 mm<sup>2</sup>

### Connection



Note miniature fuse to IEC60127-2 sheet 1  $\leq$  2 A fast acting

Core colors :

BN =

brown

BU =

blue