




Inductive sensor

IGB2008BARKA/BS-400B



Product characteristics

Output function	normally open
Sensing range [mm]	8
Housing	Threaded type
Dimensions [mm]	M18 x 1 / L = 53

Application

Special feature	Increased sensing range
-----------------	-------------------------

Electrical data

Operating voltage [V]	20...140 AC/DC
Protection class	II
Reverse polarity protection	yes

Outputs

Output function	normally open
Max. voltage drop switching output DC [V]	6
Max. voltage drop switching output AC [V]	6.5
Minimum load current [mA]	5
Max. leakage current [mA]	1
Permanent current rating of switching output AC [mA]	200
Permanent current rating of switching output DC [mA]	200
Short-time current rating of switching output [mA]	1200; (20ms / 0,5Hz; for UL application: $\hat{I}$: 0,9 A (20 ms / 0,5 Hz))
Switching frequency AC [Hz]	25
Switching frequency DC [Hz]	100
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Monitoring range

Sensing range [mm]	8
Operating distance [mm]	0...6.48
Increased sensing range	yes

IG0402



Inductive sensor

IGB2008BARKA/BS-400B

Accuracy / deviations		
Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminum: 0.3 / copper: 0.2	
Hysteresis	[% of Sr]	3...15
Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 67
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	1 kV line to line, Ri: 2 Ohm
	EN 61000-4-6 HF conducted	10 V
	EN 55011 emission	class B
MTTF	[years]	400
UL approval	Ta	-25...70 °C
	Enclosure type	Type 1
	File number UL	E174191
Mechanical data		
Weight	[g]	50.5
Housing		Threaded type
Mounting		flush mountable
Dimensions	[mm]	M18 x 1 / L = 53
Thread designation		M18 x 1
Material		housing: brass white bronze coated; sensing face: PBT
Displays / operating elements		
Display	Switching status	1 x LED, red
Accessories		
Items supplied		lock nuts: 2
Remarks		
Pack quantity		1 pcs.

IG0402



Inductive sensor

IGB2008BARKA/BS-400B

Electrical connection - plug

Connector: 1 x M12; coding: B

