


IG5910



Inductive sensor

IGA3008BFPKG/SS-000-K/400mA



Product characteristics		
Electrical design		PNP
Output function		normally open / closed; (selectable)
Sensing range	[mm]	8
Housing		Threaded type
Dimensions	[mm]	M18 x 1 / L = 95
Electrical data		
Operating voltage	[V]	10...36 DC
Current consumption	[mA]	15; (24 V)
Protection class		II
Reverse polarity protection		yes
Outputs		
Electrical design		PNP
Output function		normally open / closed; (selectable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	400
Switching frequency DC	[Hz]	250
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes
Monitoring range		
Sensing range	[mm]	8

IG5910



Inductive sensor

IGA3008BFPKG/SS-000-KI/400mA

Real sensing range Sr	[mm]	8 ± 10 %
Operating distance	[mm]	0...6.5

Accuracy / deviations		
Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminum: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	3...10
Switch-point drift	[% of Sr]	-18...18

Operating conditions		
Ambient temperature	[°C]	-32...70
Protection		IP 67

Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011	class B
MTTF	[years]	1283

Mechanical data		
Weight	[g]	88.9
Housing		Threaded type
Mounting		flush mountable
Dimensions	[mm]	M18 x 1 / L = 95
Thread designation		M18 x 1
Material		housing: brass white bronze coated; sensing face: PC


Displays / operating elements		
Display	Switching status	1 x LED, yellow

Accessories		
Items supplied		lock nuts: 2

Remarks		
Remarks		normally open/closed programmable by using a jumper
Pack quantity		1 pcs.

Electrical connection - plug

Connector: 1 x valve type A DIN (DIN EN 175301-803)



IG5910



Inductive sensor

IGA3008BFPKG/SS-000-K/400mA

Connection

