


# IG5930



## Inductive sensor

IGK3008BBPKG/US-104



### Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | PNP              |
| Output function    | normally open    |
| Sensing range [mm] | 8                |
| Housing            | Threaded type    |
| Dimensions [mm]    | M18 x 1 / L = 60 |

### Application

|                 |                         |
|-----------------|-------------------------|
| Special feature | gold-plated contacts    |
| Application     | Industrial applications |

### Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...30 DC |
| Current consumption [mA]    | < 10       |
| Protection class            | II         |
| Reverse polarity protection | yes        |

### Outputs

|                                                      |                    |
|------------------------------------------------------|--------------------|
| Electrical design                                    | PNP                |
| Output function                                      | normally open      |
| Max. voltage drop switching output DC [V]            | 2.5                |
| Permanent current rating of switching output DC [mA] | 200                |
| Switching frequency DC [Hz]                          | 400                |
| Short-circuit protection                             | yes                |
| Type of short-circuit protection                     | yes (non-latching) |
| Overload protection                                  | yes                |

### Monitoring range

|                            |          |
|----------------------------|----------|
| Sensing range [mm]         | 8        |
| Real sensing range Sr [mm] | 8 ± 10 % |
| Operating distance [mm]    | 0...6.48 |

### Accuracy / deviations

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| Correction factor    | steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminum: 0.4 / copper: 0.3 |
| Hysteresis [% of Sr] | 1...20                                                                     |

# IG5930



## Inductive sensor

IGK3008BBPKG/US-104

|                    |           |          |
|--------------------|-----------|----------|
| Switch-point drift | [% of Sr] | -10...10 |
|--------------------|-----------|----------|

### Operating conditions

|                     |      |          |
|---------------------|------|----------|
| Ambient temperature | [°C] | -25...70 |
|---------------------|------|----------|

|            |       |
|------------|-------|
| Protection | IP 68 |
|------------|-------|

### Tests / approvals

|     |                           |                                |
|-----|---------------------------|--------------------------------|
| EMC | EN 61000-4-2 ESD          | 4 kV CD / 8 kV AD              |
|     | EN 61000-4-3 HF radiated  | 10 V/m                         |
|     | EN 61000-4-4 Burst        | 2 kV                           |
|     | EN 61000-4-5 Surge        | 0,5 kV line to line, Ri: 2 Ohm |
|     | EN 61000-4-6 HF conducted | 10 V                           |
|     | EN 55011                  | class B                        |

|      |         |      |
|------|---------|------|
| MTTF | [years] | 1083 |
|------|---------|------|

### Mechanical data

|        |     |      |
|--------|-----|------|
| Weight | [g] | 47.4 |
|--------|-----|------|

|         |               |
|---------|---------------|
| Housing | Threaded type |
|---------|---------------|

|          |                 |
|----------|-----------------|
| Mounting | flush mountable |
|----------|-----------------|

|            |      |                  |
|------------|------|------------------|
| Dimensions | [mm] | M18 x 1 / L = 60 |
|------------|------|------------------|

|                    |         |
|--------------------|---------|
| Thread designation | M18 x 1 |
|--------------------|---------|

|          |                                                                                                                       |
|----------|-----------------------------------------------------------------------------------------------------------------------|
| Material | housing: brass white bronze coated; sensing face: LCP white;<br>LED window: PEI; lock nuts: brass white bronze coated |
|----------|-----------------------------------------------------------------------------------------------------------------------|

|                   |      |    |
|-------------------|------|----|
| Tightening torque | [Nm] | 25 |
|-------------------|------|----|

### Displays / operating elements

|         |                  |                 |
|---------|------------------|-----------------|
| Display | Switching status | 4 x LED, yellow |
|---------|------------------|-----------------|

### Accessories

|                |              |
|----------------|--------------|
| Items supplied | lock nuts: 2 |
|----------------|--------------|

### Remarks

|               |        |
|---------------|--------|
| Pack quantity | 1 pcs. |
|---------------|--------|

### Electrical connection - plug

Connector: 1 x M12; coding: A; Contacts: 3, gold-plated



# IG5930



## Inductive sensor

IGK3008BBPKG/US-104

### Connection

