




## Inductive sensor

IGK3012-BPKG/US-104



### Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | PNP              |
| Output function    | normally open    |
| Sensing range [mm] | 12               |
| Housing            | Threaded type    |
| Dimensions [mm]    | M18 x 1 / L = 60 |

### Application

|                 |                                               |
|-----------------|-----------------------------------------------|
| Special feature | gold-plated contacts; Increased sensing range |
| Application     | Industrial applications; Oils and coolants    |

### Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...30 DC |
| Current consumption [mA]    | < 10       |
| Protection class            | II         |
| Reverse polarity protection | yes        |

### Outputs

|                                                      |               |
|------------------------------------------------------|---------------|
| Electrical design                                    | PNP           |
| Output function                                      | normally open |
| Max. voltage drop switching output DC [V]            | 2.5           |
| Permanent current rating of switching output DC [mA] | 200           |
| Switching frequency DC [Hz]                          | 300           |
| Short-circuit protection                             | yes           |
| Overload protection                                  | yes           |

### Monitoring range

|                            |           |
|----------------------------|-----------|
| Sensing range [mm]         | 12        |
| Real sensing range Sr [mm] | 12 ± 10 % |
| Operating distance [mm]    | 0...9.72  |
| Increased sensing range    | yes       |

### Accuracy / deviations

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Correction factor            | steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminum: 0.4 / copper: 0.3 |
| Hysteresis [% of Sr]         | 3...15                                                                     |
| Switch-point drift [% of Sr] | -10...10                                                                   |

# IGC220



## Inductive sensor

IGK3012-BPKG/US-104

| Operating conditions                                                                |                           |                                                                                                                       |
|-------------------------------------------------------------------------------------|---------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Ambient temperature                                                                 | [°C]                      | -25...70                                                                                                              |
| Protection                                                                          |                           | IP 68; ("Coolant")                                                                                                    |
| Tests / approvals                                                                   |                           |                                                                                                                       |
| EMC                                                                                 | EN 61000-4-2 ESD          | 4 kV CD / 8 kV AD                                                                                                     |
|                                                                                     | EN 61000-4-3 HF radiated  | 10 V/m                                                                                                                |
|                                                                                     | EN 61000-4-4 Burst        | 2 kV                                                                                                                  |
|                                                                                     | EN 61000-4-6 HF conducted | 10 V                                                                                                                  |
|                                                                                     | EN 55011                  | class B                                                                                                               |
| MTTF                                                                                | [years]                   | 1083                                                                                                                  |
| Embedded software included                                                          |                           | no                                                                                                                    |
| UL approval                                                                         | Ta                        | 0...40 °C                                                                                                             |
|                                                                                     | Enclosure type            | Type 1                                                                                                                |
|                                                                                     | UL approval number        | A004                                                                                                                  |
|                                                                                     | File number UL            | E174191                                                                                                               |
| Mechanical data                                                                     |                           |                                                                                                                       |
| Weight                                                                              | [g]                       | 47.5                                                                                                                  |
| Housing                                                                             |                           | Threaded type                                                                                                         |
| Mounting                                                                            |                           | non-flush mountable                                                                                                   |
| Dimensions                                                                          | [mm]                      | M18 x 1 / L = 60                                                                                                      |
| Thread designation                                                                  |                           | M18 x 1                                                                                                               |
| Material                                                                            |                           | housing: brass white bronze coated; sensing face: LCP white;<br>LED window: PEI; lock nuts: brass white bronze coated |
| Displays / operating elements                                                       |                           |                                                                                                                       |
| Display                                                                             | Switching status          | 4 x 90° LED, yellow                                                                                                   |
| Accessories                                                                         |                           |                                                                                                                       |
| Items supplied                                                                      |                           | lock nuts: 2                                                                                                          |
| Remarks                                                                             |                           |                                                                                                                       |
| Pack quantity                                                                       |                           | 1 pcs.                                                                                                                |
| Electrical connection - plug                                                        |                           |                                                                                                                       |
| Connector: 1 x M12; coding: A; Contacts: 3, gold-plated                             |                           |                                                                                                                       |
|  |                           |                                                                                                                       |



## Inductive sensor

IGK3012-BPKG/US-104

### Connection

