




## Inductive full-metal sensor

IGB3008BBPKG/AM/2M/PUR



1 LED yellow



### Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | PNP              |
| Output function    | normally open    |
| Sensing range [mm] | 8                |
| Housing            | Threaded type    |
| Dimensions [mm]    | M18 x 1 / L = 40 |

### Application

|                         |                                                                     |
|-------------------------|---------------------------------------------------------------------|
| Special feature         | Drag chain suitability; Increased sensing range; Full-metal housing |
| Application             | Industrial applications; Oils and coolants                          |
| Pressure rating         | 20 bar 2 MPa                                                        |
| Note on pressure rating | sensing face                                                        |

### Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...30 DC |
| Current consumption [mA]    | < 10       |
| Protection class            | III        |
| Reverse polarity protection | yes        |

### Outputs

|                                                      |               |
|------------------------------------------------------|---------------|
| Electrical design                                    | PNP           |
| Output function                                      | normally open |
| Max. voltage drop switching output DC [V]            | 2.5           |
| Permanent current rating of switching output DC [mA] | 100           |
| Switching frequency DC [Hz]                          | 100           |
| Short-circuit protection                             | yes           |
| Overload protection                                  | yes           |

### Monitoring range

|                               |               |
|-------------------------------|---------------|
| Sensing range [mm]            | 8             |
| Real sensing range $S_r$ [mm] | $8 \pm 10 \%$ |
| Operating distance [mm]       | 0...6.48      |
| Increased sensing range       | yes           |

### Accuracy / deviations

|                   |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| Correction factor | steel: 1 / stainless steel: 0.7 / brass: 0.6 / aluminum: 0.5 / copper: 0.2 |
|-------------------|----------------------------------------------------------------------------|

# IGC261



## Inductive full-metal sensor

IGB3008BBPKG/AM/2M/PUR

|                    |           |          |
|--------------------|-----------|----------|
| Hysteresis         | [% of Sr] | 3...15   |
| Switch-point drift | [% of Sr] | -10...10 |

### Operating conditions

|                     |      |                                    |
|---------------------|------|------------------------------------|
| Ambient temperature | [°C] | -40...85                           |
| Protection          |      | IP 65; IP 66; IP 67; IP 68; IP 69K |

### Tests / approvals

|                             |                           |                                                                                    |
|-----------------------------|---------------------------|------------------------------------------------------------------------------------|
| EMC                         | EN 61000-4-2 ESD          | 4 kV CD / 8 kV AD                                                                  |
|                             | EN 61000-4-3 HF radiated  | 10 V/m                                                                             |
|                             | EN 61000-4-4 Burst        | 2 kV                                                                               |
|                             | EN 61000-4-6 HF conducted | 10 V                                                                               |
|                             | EN 55011                  | class B                                                                            |
| Impact resistance           |                           | 1 J                                                                                |
| Vibration resistance        | EN 60068-2-6 Fc           | 20 g (10...3000 Hz) / 50 sweep cycles per frequency; 1 octave per minute in 3 axes |
| Shock resistance            | EN 60068-2-27 Ea          | 100 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes   |
| Continuous shock resistance | EN 60068-2-27             | 40 g 6 ms; 4000 shocks each in every direction of the 3 coordinate axes            |
| Fast temperature changes    | EN 60068-2-14 Na          | TA = -40 °C; TB = 85 °C; t1 = 30 min; t2 = < 10 s; 50 cycles                       |
| Salt spray test             | EN 60068-2-52 Kb          | severity level 5 (4 test cycles)                                                   |
| MTTF                        | [years]                   | 1258                                                                               |
| Embedded software included  |                           | yes                                                                                |
| UL approval                 | Ta                        | -25...75 °C                                                                        |
|                             | Enclosure type            | Type 1                                                                             |
|                             | voltage supply            | Limited Voltage/Current                                                            |
|                             | UL approval number        | A018                                                                               |
|                             | File number UL            | E174191                                                                            |

### Mechanical data

|                        |                                          |                                                                                                                                       |
|------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Weight                 | [g]                                      | 91                                                                                                                                    |
| Housing                |                                          | Threaded type                                                                                                                         |
| Mounting               |                                          | flush mountable                                                                                                                       |
| Dimensions             | [mm]                                     | M18 x 1 / L = 40                                                                                                                      |
| Thread designation     |                                          | M18 x 1                                                                                                                               |
| Material               |                                          | stainless steel (1.4404 / 316L); sensing face: stainless steel (1.4404 / 316L); LED window: PEI; lock nuts: brass white bronze coated |
| Tightening torque      | [Nm]                                     | 50                                                                                                                                    |
| Drag chain suitability |                                          | yes                                                                                                                                   |
| Drag chain suitability | Bending radius for flexible applications | min. 10 x cable diameter                                                                                                              |
|                        | Bending cycles                           | > 5 Mio.                                                                                                                              |
| Full-metal housing     |                                          | yes                                                                                                                                   |

### Displays / operating elements

|         |                  |             |
|---------|------------------|-------------|
| Display | Switching status | LED, yellow |
|---------|------------------|-------------|

### Accessories

|                |  |              |
|----------------|--|--------------|
| Items supplied |  | lock nuts: 2 |
|----------------|--|--------------|

### Remarks

|               |  |        |
|---------------|--|--------|
| Pack quantity |  | 1 pcs. |
|---------------|--|--------|

# IGC261




## Inductive full-metal sensor

IGB3008BBPKG/AM/2M/PUR

### Electrical connection

Cable: 2 m, PUR, Ø 4 mm; burning behaviour to ECE R118 rev. 2; 3 x 0.34 mm<sup>2</sup>

### Connection



|    |             |
|----|-------------|
|    | Core colors |
| BK | black       |
| BN | brown       |
| BU | blue        |