


IM0053



Inductive sensor

IMC2035-ABOA/SL/LS-100FK



Product characteristics

Output function		normally open
Sensing range	[mm]	35
Housing		rectangular
Dimensions	[mm]	40 x 40 x 66

Application

Special feature	gold-plated contacts; Increased sensing range
-----------------	---

Electrical data

Operating voltage	[V]	20...250 AC/DC
Protection class		I
Reverse polarity protection		no

Outputs

Output function		normally open
Max. voltage drop switching output DC	[V]	6
Max. voltage drop switching output AC	[V]	6.5
Minimum load current	[mA]	1.9
Max. leakage current	[mA]	2.5 (250 V AC) / 1.3 (130 V AC) / 0.8 (24 V DC)
Permanent current rating of switching output AC	[mA]	250; (350 (...50 °C))



Inductive sensor

IMC2035-ABOA/SL/LS-100FK

Permanent current rating of switching output DC	[mA]	100
Short-time current rating of switching output	[mA]	2200; (20 ms / 0,5 Hz)
Switching frequency AC	[Hz]	20
Switching frequency DC	[Hz]	50
Short-circuit proof		no
Overload protection		no

Monitoring range		
Sensing range	[mm]	35
Operating distance	[mm]	0...28.3
Increased sensing range		yes

Accuracy / deviations		
Correction factor		steel: 1 / stainless steel: 0.8 / brass: 0.4 / aluminum: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	3...15

Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 67

Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011	class B
MTTF	[years]	600

Mechanical data		
Weight	[g]	167.15
Housing		rectangular
Mounting		non-flush mountable
Dimensions	[mm]	40 x 40 x 66
Material		housing: PPE; sensing face: PPE orange; bevelled housing part: PPS; clamp: PPS black; screw: steel galvanized

Displays / operating elements		
Display	Switching status	1 x LED, yellow

Electrical connection	
Required protection	miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting

Remarks	
Remarks	Recommendation: check the unit for reliable function after a short circuit. 5 positions of the active zone possible
Pack quantity	1 pcs.

IM0053




Inductive sensor

IMC2035-ABOA/SL/LS-100FK

Electrical connection - plug

Connector: 1 x M12; coding: C; Locking: brass, white bronze coated; Contacts: gold-plated



Note miniature fuse to IEC60127-2 sheet 1 ≤ 2 A fast acting