




Capacitive sensor

KB-2020-ABOA/NI

RT



Product characteristics

Output function	normally open
Sensing range [mm]	3...20
Housing	tubular
Dimensions [mm]	Ø 34 / L = 81

Electrical data

Operating voltage [V]	20...250 AC/DC
Protection class	II
Reverse polarity protection	no

Outputs

Output function	normally open
Max. voltage drop switching output DC [V]	8
Max. voltage drop switching output AC [V]	10
Minimum load current [mA]	5
Max. leakage current [mA]	2.5 (250 V AC) / 1.7 (110 V AC) / 1.5 (24 V DC)
Permanent current rating of switching output AC [mA]	200; (for UL application: 250 / 100 DC)
Permanent current rating of switching output DC [mA]	200; (for UL application: 250 AC / 100 DC)
Short-time current rating of switching output [mA]	1500; (20 ms / 0,5 Hz)
Switching frequency AC [Hz]	25
Switching frequency DC [Hz]	40
Short-circuit proof	no
Overload protection	no

Monitoring range

Sensing range [mm]	3...20
Sensing range adjustable	yes
Factory setting sensing range [mm]	20
Real sensing range Sr [mm]	20 ± 10 %
Operating distance [mm]	0...16.2

Accuracy / deviations

Correction factor	glass: 0.4 / water: 1 / ceramics: 0.2 / PVC: 0.2
-------------------	--



Capacitive sensor

KB-2020-ABOA/NI RT

Hysteresis	[% of Sr]	1...15
Switch-point drift	[% of Sr]	-15...15

Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 65
Increased immunity		yes; (Increased immunity to conducted radio frequency interference)

Tests / approvals		
EMC	EN 60947-5-2	
MTTF	[years]	488

Mechanical data		
Weight	[g]	258
Housing		tubular
Mounting		non-flush mountable
Dimensions	[mm]	Ø 34 / L = 81
Material		housing: PBT

Displays / operating elements		
Display	Switching status	1 x LED, red


Electrical connection		
Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting

Accessories		
Items supplied		Mounting clamp: 2
		cylinder screws: 2
		spring discs: 2

Remarks		
Remarks		Recommendation: check the unit for reliable function after a short circuit.
Pack quantity		1 pcs.

Electrical connection		
Cable: 2 m, PVC; 2 x 0.5 mm²		

Connection		
------------	--	--



Note miniature fuse to IEC60127-2 sheet 1 ≤ 2 A fast acting
Core colors :
BN = brown
BU = blue