


MGT201



Magnetic sensor

MGK3100-BPKG/M/V4A/US-104-DPS



Product characteristics		
Electrical design		PNP
Output function		normally open
Sensing range	[mm]	100; (referred to magnet M 4.0)
Housing		Threaded type
Dimensions	[mm]	M18 x 1 / L = 60
Application		
Special feature		gold-plated contacts
Application		pig detection
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 10
Protection class		III
Reverse polarity protection		yes
Outputs		
Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	200
Short-circuit protection		yes
Overload protection		yes
Monitoring range		
Sensing range	[mm]	100; (referred to magnet M 4.0)
Magnetic sensitivity	[mT]	0.3
Accuracy / deviations		
Hysteresis	[% of Sr]	1...10
Reaction times		
Pulse stretching	[ms]	1000

MGT201



Magnetic sensor

MGK3100-BPKG/M/V4A/US-104-DPS

Operating conditions

Ambient temperature	[°C]	0...104
Protection		IP 68; IP 69K

Tests / approvals

EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	0,5 kV line to line, Ri: 2 Ohm
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
MTTF	[years]	1445

Mechanical data

Weight	[g]	47.3
Housing		Threaded type
Dimensions	[mm]	M18 x 1 / L = 60
Thread designation		M18 x 1
Material		housing: stainless steel (1.4404 / 316L); sensing face: PEEK; lock nuts: stainless steel

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	lock nuts: 2
----------------	--------------

Remarks

Remarks	voltage supply to EN50178, SELV, PELV
Pack quantity	1 pcs.

Electrical connection - plug

Connector: 1 x M12; coding: A; Contacts: 4, gold-plated



Connection

