

MK5108



T-slot cylinder sensor

MKT3028BBPKG/G/0,3M/ZH/US

Operating conditions

Ambient temperature	[°C]	-25...85
Protection		IP 65; IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD	- CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
MTTF	[years]	3694
UL approval	Enclosure type	Type 1
	UL approval number	C003

Mechanical data

Weight	[g]	21
Mounting		flush mountable
Type of mounting		fastening clamp with combined slot / hexagon socket, width across flats 1.5
Cylinder type		T-slot cylinders
Dimensions	[mm]	25 x 5 x 6.5
Material		housing: PA; Fastening clamp: stainless steel

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	rubber memory stop: 1
	cable clip: 1

Remarks

Remarks	cULus - Class 2 source required; enclosure type 1
Pack quantity	1 pcs.

Electrical connection - plug

Cable: 0.3 m, PUR

Connector: 1 x M12; coding: A; Contacts: 4; Locking: Knurled nut, rotatable



MK5108



T-slot cylinder sensor

MKT3028BBPKG/G/0,3M/ZH/US

Connection

