

MQ2005




Magnetic sensor

MQ23005BFRKG/B/AM/IO/0,3M/ZH/US

Article to be discontinued
Discontinuation date: 03/31/2025

Alternative articles: IQ2012
When selecting an alternative article and accessories please note that technical data may differ!



- 1 LED yellow
- 2 LED green



Product characteristics	
Electrical design	PNP/NPN; (configurable)
Output function	normally open / closed; (configurable)
Sensing range [mm]	5
Communication interface	IO-Link
Housing	rectangular
Dimensions [mm]	20 x 8 x 32
Application	
Application	Industrial applications; Ferrous only
Electrical data	
Operating voltage [V]	10...30 DC
Rated insulation voltage [V]	60



Magnetic sensor

MQ23005BFRKG/B/AM/IO/0,3M/ZH/US

Current consumption	[mA]	< 30
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	< 0.3

Outputs

Electrical design		PNP/NPN; (configurable)
Output function		normally open / closed; (configurable)
Max. voltage drop switching output DC	[V]	2.5
Max. leakage current	[mA]	0.1
Permanent current rating of switching output DC	[mA]	100
Short-time current rating of switching output	[mA]	100
Switching frequency DC	[Hz]	200
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Sensing range	[mm]	5
Real sensing range Sr	[mm]	5 ± 10 %
Operating distance	[mm]	0...4.05

Accuracy / deviations

Correction factor		steel: 1
Hysteresis	[% of Sr]	< 10
Switch-point drift	[% of Sr]	-10...20
Repeatability	[% of Sr]	10

Software / programming

Parameter setting options		hysteresis / window; switch-off delay; switch-on operations; Auto-teach
---------------------------	--	---

Interfaces

Communication interface		IO-Link
Transmission type		COM2 (38,4 kBaud)
IO-Link revision		1.1
SDCI standard		IEC 61131-9 CDV
Profiles	Smart Sensor - SSP 0	Generic Profiled Sensor
	Common - I&D	Identification and Diagnosis
	Function	Multiple switching signal
	Function	Teach channel
SIO mode		yes
Required master port class		A
Min. process cycle time	[ms]	9.6
IO-Link process data (cyclical)	Function	bit length
	process value	16
	device status	4
	binary switching information	4

MQ2005



Magnetic sensor

MQ23005BFRKG/B/AM/IO/0,3M/ZH/US

IO-Link functions (acyclical)	application specific tag; operating hours counter; switching cycles counter	
Supported DeviceIDs	Type of operation	DeviceID
	default	830
Note	For further information please see the IODD PDF file at "Downloads"	

Operating conditions

Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-30...85
Protection		IP 65; IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
Vibration resistance	EN 60068-2-6 Fc	20 g (10...3000 Hz) / 50 sweep cycles per frequency; 1 octave per minute in 3 axes
Shock resistance	EN 60068-2-27 Ea	100 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes
Continuous shock resistance	EN 60068-2-27	40 g 6 ms; 4000 shocks each in every direction of the 3 coordinate axes
MTTF	[years]	1976
UL approval	Ta	-25...60 °C
	Enclosure type	Type 1
	voltage supply	Limited Voltage/Current
	UL approval number	C010
	File number UL	E174191

Mechanical data

Weight	[g]	44.9
Housing		rectangular
Mounting		flush mountable
Dimensions	[mm]	20 x 8 x 32
Material		diecast zinc; LED window: TPU (urethane); potting: PUR

Displays / operating elements

Display	Display operation	1 x LED, green
	Switching status	1 x LED, yellow

Remarks

Pack quantity	1 pcs.
---------------	--------

MQ2005





Magnetic sensor

MQ23005BFRKG/B/AM/IO/0,3M/ZH/US

Electrical connection

Cable: 0.3 m, PUR, Ø 4.9 mm; flame-retardant (IEC 60332-2, UL: FT2)

Connection



4 OUT / IO-Link

Connector: 1 x M12; coding: A; Contacts: 3; Locking: Knurled nut, rotatable

