


O4S500



Through-beam sensor transmitter

O4S-00KG/US100



Product characteristics	
Type of light	red light
Housing	rectangular
Application	
Function principle	Through-beam sensor
Application	Industrial applications
Electrical data	
Operating voltage [V]	10...36 DC; (cULus - Class 2 source required)
Current consumption [mA]	20
Protection class	II
Reverse polarity protection	yes
Type of light	red light
Wave length [nm]	624
Outputs	
Overload protection	yes

O4S500



Through-beam sensor transmitter

O4S-00KG/US100

Monitoring range	
Transmitter / receiver	transmitter
Range [m]	0...80
Range adjustable	no
Max. light spot diameter [mm]	2400
Light spot dimensions refer to	at maximum range

Operating conditions	
Ambient temperature [°C]	-25...60
Protection	IP 67

Tests / approvals	
EMC	EN 60947-5-2
MTTF [years]	616

Mechanical data	
Weight [g]	122
Housing	rectangular
Dimensions [mm]	74.4 x 27 x 63.8
Material	operator interface: TPE; housing: PA; Front framework: stainless steel
Lens material	front lens:PMMA
Lens alignment	Side sensing

Mounting hole	
Tightening torque [Nm]	< 2; (when using a mounting screw M5)

Displays / operating elements	
Display	Power 1 x LED, green


Remarks	
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M12; coding: A; Contacts: 4



Connection



O4S500




Through-beam sensor transmitter

O4S-OOKG/US100

Diagrams and graphs

excess gain graph



x: Abstand [mm]

y: Funktionsreservefaktor