


OGP103



Retro-reflective sensor

OGP-HNKG/US



Product characteristics

Type of light	red light
Housing	Threaded type

Application

Special feature	polarization filter
Function principle	Retro-reflective sensor
Application	For use in conveying and materials handling

Electrical data

Operating voltage	[V]	10...30 DC
Current consumption	[mA]	20
Protection class		III
Reverse polarity protection		yes
Type of light		red light

Outputs

Electrical design		NPN
Output function		light-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	200
Switching frequency DC	[Hz]	1000
Short-circuit protection		yes
Overload protection		yes

Monitoring range

Range referred to prismatic reflector	[m]	0.05...2.5; (Prismatic reflector Ø 80 E20005)
Range adjustable		no
Max. light spot diameter	[mm]	200
Light spot dimensions refer to		at maximum range
Polarization filter available		yes

Operating conditions

Ambient temperature	[°C]	-25...60
---------------------	------	----------



Retro-reflective sensor

OGP-HNKG/US

Protection	IP 67; (in conjunction with a corresponding connector)
------------	--

Tests / approvals

EMC	EN 60947-5-2	
MTTF	[years]	1161

Mechanical data

Weight	[g]	14.8
Housing		Threaded type
Dimensions	[mm]	M18 x 1 / L = 44
Thread designation		M18 x 1
Material		housing: ABS
Lens material		front lens:PMMA

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	lock nuts: 2
----------------	--------------

Remarks


Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: 4



Connection






Retro-reflective sensor

OGP-HNKG/US

Diagrams and graphs

excess gain graph



x: distance [mm]

y: excess gain factor