


OK5002

Fiber-optic amplifier

OKF-FNKG



Product characteristics

Type of light	red light
Housing	rectangular

Application

Application	Industrial applications
-------------	-------------------------

Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	30; ((24 V))
Protection class		III
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	660

Outputs

Electrical design		NPN
Output function		light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	120
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Range	[m]	0...0.12; (Through-beam sensor)
Range	[mm]	0...40; (Diffuse reflection sensor)
Range adjustable		yes

Operating conditions

Ambient temperature	[°C]	-25...60
Protection		IP 65



OK5002



Fiber-optic amplifier

OKF-FNKG

Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011	class B
MTTF	[years]	529
Mechanical data		
Weight	[g]	150
Housing		rectangular
Dimensions	[mm]	50 x 19 x 35
Number of channels		1
Material		PPO modified
Displays / operating elements		
Display	Switching status	1 x LED, yellow
Accessories		
Items supplied	screwdrivers	
	screws: 2 x (M4 x 25 mm)	
	washers: 2	
	spring washers: 2	
	Nuts: 2	
Remarks		
Remarks	light-on mode corresponds to the NC output function for through-beam fibers	
	corresponds to the NO output function for diffuse-reflection fibers	
	dark-on mode corresponds to the NO output function for through-beam fibers	
	corresponds to the NC output function for diffuse-reflection fiber optics	
Pack quantity	1 pcs.	
Electrical connection		
Cable: 2 m, PVC; 4 x 0.34 mm²		
Connection		



Core colors :
BN = brown
BU = blue
BK = black
WH = white