




Through-beam sensor receiver

OUE-DPKG/US-100-DPS



Product characteristics

Type of light	Infrared light
Housing	rectangular

Application

Function principle	Through-beam sensor
Application	Industrial applications

Electrical data

Operating voltage	[V]	10...55 DC; (cULus - Class 2 source required)
Current consumption	[mA]	20; ((24 V))
Protection class		III
Reverse polarity protection		yes
Type of light		Infrared light
Wave length	[nm]	880

Outputs

Electrical design		PNP
Output function		dark-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	140
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Transmitter / receiver		receiver
Range	[m]	< 6
Range adjustable		yes

Operating conditions

Ambient temperature	[°C]	-25...80
---------------------	------	----------



Through-beam sensor receiver

OUE-DPKG/US-100-DPS

Protection	IP 67
------------	-------

Tests / approvals

EMC	EN 60947-5-2	
MTTF [years]	618	
UL approval	Ta	< 40 °C
	Enclosure type	Type 1
	voltage supply	Class 2
	UL approval number	E032
	File number UL	E174191

Mechanical data

Weight [g]	73
Housing	rectangular
Dimensions [mm]	28 x 16 x 51
Number of channels	1
Material	housing: PPO modified
Lens material	front lens:glass

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	Angle bracket: 1, E20211
----------------	--------------------------


Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: 4

Connection





Through-beam sensor receiver

OUE-DPKG/US-100-DPS

Diagrams and graphs

excess gain graph

