




Diffuse reflection sensor

OUN-HPKG/US-100-DPS



Receiver in upper lens
transmitter in lower lens



Product characteristics

Type of light	Infrared light
Housing	rectangular

Application

Special feature	short ranges
Function principle	Diffuse reflection sensor
Application	Industrial applications

Electrical data

Operating voltage	[V]	10...55 DC; (cULus - Class 2 source required)
Current consumption	[mA]	35; ((24 V))
Protection class		III
Reverse polarity protection		yes
Type of light		Infrared light
Wave length	[nm]	880

Outputs

Electrical design		PNP
Output function		light-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	160
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Range	[mm]	20...40; (white paper 200 x 200 mm)
Max. light spot diameter	[mm]	20
Light spot dimensions refer to		at maximum range
Short ranges		yes



Diffuse reflection sensor

OUN-HPKG/US-100-DPS

Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67

Tests / approvals		
EMC	EN 60947-5-2	
MTTF	[years]	685
UL approval	Ta	< 40 °C
	Enclosure type	Type 1
	voltage supply	Class 2
	UL approval number	E032
	File number UL	E174191

Mechanical data		
Weight	[g]	70.5
Housing		rectangular
Dimensions	[mm]	28 x 16 x 51
Number of channels		1
Material		housing: PPO modified
Lens material		front lens:glass

Displays / operating elements		
Display	Switching status	1 x LED, yellow

Accessories		
Items supplied		Angle bracket: 1, E20211


Remarks		
Pack quantity		1 pcs.

Electrical connection

Connector: 1 x M12; coding: A; Contacts: 4



Connection





Diffuse reflection sensor

OUN-HPKG/US-100-DPS

Diagrams and graphs

excess gain graph

