


PE2096



Pressure sensor with display

PE-2,5-RER14-MFRKG/US/ /E



KTW/W270 Reg31



Product characteristics

Number of inputs and outputs	Number of digital outputs: 2; Number of analog outputs: 1			
Measuring range	-0.125...2.5 bar	-125...2500 mbar	-1.8...36.25 psi	-12.5...250 kPa
Process connection	threaded connection G 1/4 Internal thread			

Application

Special feature	gold-plated contacts		
Measuring element	ceramic-capacitive pressure measuring cell		
Application	for industrial applications		
Media	liquids and gases		
Medium temperature [°C]	-25...80		
Min. burst pressure	50 bar	725 psi	5000 kPa
Pressure rating	20 bar	290 psi	2000 kPa
Vacuum resistance	-1000 mbar		-0.1 MPa
Type of pressure	relative pressure		

Electrical data

Operating voltage [V]	18...30 DC; (to SELV/PELV)
Current consumption [mA]	< 35
Min. insulation resistance [MΩ]	100; (500 V DC)
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	0.3
Integrated watchdog	yes



Pressure sensor with display

PE-2,5-RER14-MFRKG/US/ /E

Inputs / outputs				
Number of inputs and outputs		Number of digital outputs: 2; Number of analog outputs: 1		
Outputs				
Total number of outputs		2		
Output signal		switching signal; analog signal; IO-Link; (configurable)		
Electrical design		PNP/NPN		
Number of digital outputs		2		
Output function		normally open / closed; (configurable)		
Max. voltage drop switching output DC	[V]	2		
Permanent current rating of switching output DC	[mA]	250		
Switching frequency DC	[Hz]	< 500		
Number of analog outputs		1		
Analog current output	[mA]	4...20; (scalable 1:5)		
Max. load	[Ω]	500		
Analog voltage output	[V]	0...10; (scalable 1:5)		
Min. load resistance	[Ω]	2000		
Short-circuit protection		yes		
Type of short-circuit protection		yes (non-latching)		
Overload protection		yes		
Measuring/setting range				
Measuring range		-0.125...2.5 bar	-125...2500 mbar	-1.8...36.25 psi -12.5...250 kPa
Analog start point		-0.125...2 bar	-1.8...29 psi	-12.5...200 kPa
Analog end point		0.375...2.5 bar	5.45...36.25 psi	37.5...250 kPa
Factory setting / CMPT = 2				
Set point SP		-0.11...2.5 bar	-1.6...36.25 psi	-11...250 kPa
Reset point rP		-0.12...2.49 bar	-1.75...36.1 psi	-12...249 kPa
Min. difference between SP and rP		0.015 bar	0.15 psi	1.5 kPa
In steps of		0.005 bar	0.05 psi	0.5 kPa
Status_B High Resolution / CMPT = 3				
Set point SP		-0.109...2.5 bar	-1.58...36.25 psi	-10.9...250 kPa
Reset point rP		-0.12...2.49 bar	-1.73...36.11 psi	-12...249 kPa
Min. difference between SP and rP		0.011 bar	0.15 psi	1.1 kPa
In steps of		0.001 bar	0.01 psi	0.1 kPa
Accuracy / deviations				
Switch point accuracy [% of the span]		< ± 0,4; (Turn down 1:1)		
Repeatability [% of the span]		< ± 0,1; (with temperature fluctuations < 10 K; Turn down 1:1)		
Characteristics deviation [% of the span]		< ± 0,25 (BFSL) / < ± 0,5 (LS); (Turn down 1:1; BFSL = Best Fit Straight Line; LS = limit value setting)		
Hysteresis deviation [% of the span]		< ± 0,1; (Turn down 1:1)		
Long-term stability		< ± 0,05; (Turn down 1:1; per 6 months)		



Pressure sensor with display

PE-2,5-RER14-MFRKG/US/ /E

	[% of the span]	
Temperature coefficient zero point		0,2; (-25...80 °C)
	[% of the span / 10 K]	
Temperature coefficient span		0,2; (-25...80 °C)
	[% of the span / 10 K]	
Notes on the accuracy / deviation		switch point accuracy, linearity error under DNV GL: < ± 1%: < ± 1%

Reaction times

Response time	[ms]	< 1.5
Delay time programmable dS, dr	[s]	0...50
Damping process value dAP	[s]	0...4
Damping for the analog output dAA	[s]	0...4
Max. response time analog output	[ms]	3

Software / programming

Parameter setting options	hysteresis / window; normally open / closed; switch-on/ switch-off delay; Damping; Display unit; current/voltage output
---------------------------	---

Interfaces

Communication interface	IO-Link						
Transmission type	COM2 (38,4 kBaud)						
IO-Link revision	1.1						
SDCI standard	IEC 61131-9						
SIO mode	yes						
Required master port class	A; (when pin 2 not connected: B)						
Supported DeviceIDs	<table> <tr> <th>Type of operation</th><th>DeviceID</th></tr> <tr> <td>Factory setting / CMPT = 2</td><td>464</td></tr> <tr> <td>Status_B High Resolution / CMPT = 3</td><td>975</td></tr> </table>	Type of operation	DeviceID	Factory setting / CMPT = 2	464	Status_B High Resolution / CMPT = 3	975
Type of operation	DeviceID						
Factory setting / CMPT = 2	464						
Status_B High Resolution / CMPT = 3	975						
Note	For further information please see the IODD PDF file at "Downloads"						

Factory setting / CMPT = 2

Profiles	Smart Sensor - SSP 0		Generic Profiled Sensor	
	Function		Device identification	
	Function		Process data variable	
	Function		Device diagnosis	
Min. process cycle time	[ms]	2.3		
IO-Link resolution pressure	[bar]	0.005		
IO-Link process data (cyclical)	Function		bit length	
	pressure		14	
	binary switching information		2	
IO-Link functions (acyclical)	application specific tag			

Status_B High Resolution / CMPT = 3

Profiles	Smart Sensor - SSP 3.1	Measuring Sensor
	Common - I&D	Identification and Diagnosis
Min. process cycle time	[ms]	3
IO-Link resolution pressure	[bar]	0.001

PE2096



Pressure sensor with display

PE-2,5-RER14-MFRKG/US/ /E

IO-Link process data (cyclical)	Function	bit length
	pressure	16
	device status	4
	binary switching information	2

Operating conditions		
Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-40...100
Protection		IP 65; IP 67

Tests / approvals		
EMC	DIN EN 61000-6-2 DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	50 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	20 g (10...2000 Hz)
MTTF	[years]	171
UL approval	UL approval number	J012
Pressure equipment directive	sound engineering practice; can be used for group 2 fluids; group 1 fluids on request	

Mechanical data		
Weight	[g]	235.5
Housing		tubular
Dimensions	[mm]	Ø 34 / L = 90.7
Material		stainless steel (1.4404 / 316L); PBT+PC-GF30; PBT-GF20; PC
Materials (wetted parts)		stainless steel (1.4404 / 316L); Al2O3 (99.9 %; ceramics); EPDM
Min. pressure cycles		100 million
Tightening torque	[Nm]	25...35; (recommended tightening torque; Depends on lubrication, seal and pressure rating)
Process connection		threaded connection G 1/4 Internal thread
Restrictor element integrated		no (can be retrofitted)

Displays / operating elements		
Display	Display unit	3 x LED, green (bar, psi, kPa)
	Switching status	2 x LED, yellow
	Measured values	alphanumeric display, red/green 4-digit

Remarks		
Pack quantity		1 pcs.

Electrical connection

Connector: 1 x M12; coding: A; Contacts: 4, gold-plated



PE2096



Pressure sensor with display

PE-2,5-RER14-MFRKG/US/ /E

Connection



OUT1 switching output or IO-Link
OUT2 switching output or analog output
Colors to DIN EN 60947-5-2
Core colors :

BK = black
BN = brown
BU = blue
WH = white