


PQC819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/



Product characteristics			
Number of inputs and outputs		Number of digital outputs: 1; Number of analog outputs: 1	
Measuring range		-1...0 bar	-1000...0 mbar -100...0 kPa
Process connection		threaded connection G 1/8 Internal thread (2x)	
Application			
Special feature		gold-plated contacts	
Application		for industrial applications	
Media		compressed air; nitrogen (N2)	
Conditionally suitable for		other media on request	
Medium temperature [°C]		0...60	
Min. burst pressure		20 bar	2 MPa
Pressure rating		10 bar	1 MPa
Vacuum resistance		-1000 mbar	-0.1 MPa
Type of pressure		relative pressure; vacuum	
Electrical data			
Operating voltage [V]		18...30 DC	



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Current consumption	[mA]	< 30
Min. insulation resistance	[MΩ]	100; (500 V DC)
Protection class		III
Reverse polarity protection		yes
Overvoltage protection		yes; (< 40 V)
Power-on delay time	[s]	0.3
Integrated watchdog		yes

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 1; Number of analog outputs: 1
------------------------------	---

Outputs

Total number of outputs	2
Output signal	switching signal; analog signal; IO-Link; (configurable)
Electrical design	PNP/NPN; (configurable)
Number of digital outputs	1
Output function	normally open / closed; (configurable)
Max. voltage drop switching output DC	[V] 2.5
Permanent current rating of switching output DC	[mA] 100
Switching frequency DC	[Hz] < 170
Number of analog outputs	1
Analog current output	[mA] 4...20, invertible; (scalable)
Max. load	[Ω] 500
Analog voltage output	[V] 0...10 / 1...5, invertible; (scalable)
Min. load resistance	[Ω] 2000
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Measuring/setting range

Measuring range	-1...0 bar	-1000...0 mbar	-100...0 kPa
Set point SP	-1...0 bar		-100...0 kPa
Analog start point	-1...-0.2 bar		-100...-20 kPa
Analog end point	-0.8...0 bar		-80...0 kPa
In steps of	0.001 bar		0.1 kPa

Accuracy / deviations

Switch point accuracy	[% of the span]	< ± 1; (Turn down 1:1)
Repeatability	[% of the span]	< ± 0,1; (with temperature fluctuations < 10 K: Turn down 1:1)
Characteristics deviation	[% of the span]	< ± 1; (Turn down 1:1; including linearity, hysteresis and repeatability)
Linearity deviation	[% of the span]	< ± 1 % (limit value setting to DIN EN IEC 62828-1)
Hysteresis deviation	[% of the span]	< ± 0,25; (Turn down 1:1)
Long-term stability		< ± 0,1; (Turn down 1:1; per year)



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

	[% of the span]	
Temperature coefficient zero point		0,2; (Turn down 1:1)
	[% of the span / 10 K]	
Temperature coefficient span		0,2; (Turn down 1:1)
	[% of the span / 10 K]	

Reaction times

Response time	[ms]	6
Damping process value dAP	[s]	0...4
Damping for the analog output dAA	[s]	0...99.99

Software / programming

Parameter setting options	display can be rotated and switched off; analog output selectable and scalable; Teach function; simulation function; Diagnostic function
---------------------------	--

Interfaces

Communication interface	IO-Link	
Transmission type	COM3 (230,4 kBaud)	
IO-Link revision	1.1.3	
SDCI standard	IEC 61131-9: 2019-06	
Profiles	Smart Sensor - SSP 4.1.1	Measuring and Switching Sensor, 1 channel
	BLOB	Binary Large Object transfer
	Common - I&D	Identification and Diagnosis
	Extension	Quantity detection, switches when value exceeds the setpoint
	Function	Locator
	Function	ProductURI
SIO mode	yes	
Required master port class	A	
Process data analog	1	
Process data binary	2	
Min. process cycle time	[ms]	0.6
IO-Link resolution pressure	[bar]	0.0001
IO-Link process data (cyclical)	Function	bit length
	pressure	16
	device status	4
	SSC1.1	1
	SSC1.2	1
IO-Link functions (acyclical)	application specific tag; internal temperature; Medium temperature	
Supported DeviceIDs	Type of operation	DeviceID
	default	1726

Operating conditions

Ambient temperature	[°C]	0...60
Storage temperature	[°C]	-25...85
Protection		IP 65

Tests / approvals

EMC	DIN EN 61326-1	
Shock resistance	DIN EN 60068-2-27	50 g (11 ms)

PQC819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Vibration resistance	DIN EN 60068-2-6	20 g (10...2000 Hz)
MTTF [years]		392
UL approval	UL approval number	J067
	File number UL	E174189
Pressure equipment directive	sound engineering practice; can be used for stable gases fluid group 2	

Mechanical data		
Weight [g]		53.2
Housing		rectangular
Dimensions [mm]		37.7 x 30 x 38.6
Material		PBT; PC; TPE; NBR; FKM; brass; silicon (coated)
Materials (wetted parts)		PBT; FKM; brass; silicon (coated)
Min. pressure cycles		50 million
Process connection		threaded connection G 1/8 Internal thread (2x)

Displays / operating elements		
Display	Display 1"	128 x 96 pixels
	Switching status	1 x LED, yellow
Display unit		mbar; kPa; mmHg; kgf/cm²; %

Accessories	
Items supplied	head cap screw: 2 x (M3 x 8 mm)


Remarks	
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M8; coding: A; Contacts: 4, gold-plated



Connection



Electrical connection - plug

1	L+	
2	OUT	AO
3	L-	
4	MP	DO, IO-Link

AO: analog output; DO: digital output; MP: multi-function connection

PQC819



Pressure sensor for pneumatics

PQ-0-1BKHR18-MFPKG/AS/

Diagrams and graphs

drilling template

