


PQC862



Pressure sensor for pneumatics

PQ-010-RHR18-MFRKG/AS/



Product characteristics		
Number of inputs and outputs	Number of digital outputs: 1; Number of analog outputs: 1	
Measuring range	-1...10 bar	-14.5...145 psi
Process connection	threaded connection G 1/8 Internal thread (2x)	
Application		
Special feature	gold-plated contacts	
Application	for industrial applications	
Media	compressed air; nitrogen (N2)	
Conditionally suitable for	other media on request	
Medium temperature	0...60 °C	32...140 °F
Min. burst pressure	20 bar	290 psi
Pressure rating	15 bar	220 psi
Vacuum resistance	-1000 mbar	-14.5 psi
Type of pressure	relative pressure; vacuum	
Electrical data		
Operating voltage	[V]	18...30 DC

PQC862



Pressure sensor for pneumatics

PQ-010-RHR18-MFRKG/AS/

Current consumption	[mA]	< 30
Min. insulation resistance	[MΩ]	100; (500 V DC)
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	0.3
Integrated watchdog		yes

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 1; Number of analog outputs: 1
------------------------------	---

Outputs

Total number of outputs	2
Output signal	switching signal; analog signal; IO-Link; (configurable)
Electrical design	PNP/NPN; (configurable)
Number of digital outputs	1
Output function	normally open / closed; (configurable)
Max. voltage drop switching output DC	[V] 2.5
Permanent current rating of switching output DC	[mA] 100
Switching frequency DC	[Hz] < 170
Number of analog outputs	1
Analog current output	[mA] 4...20, invertible; (scalable)
Max. load	[Ω] 500
Analog voltage output	[V] 0...10 / 1...5, invertible; (scalable)
Min. load resistance	[Ω] 2000
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)
Overload protection	yes

Measuring/setting range

Measuring range	-1...10 bar	-14.5...145 psi
Set point SP	-1...10 bar	-14.5...145 psi
Analog start point	-1...8 bar	-14.5...116 psi
Analog end point	1...10 bar	14.5...145 psi
In steps of	0.01 bar	0.1 psi

Accuracy / deviations

Switch point accuracy		< ± 0,5; (Turn down 1:1)
	[% of the span]	
Repeatability	[% of the span]	< ± 0,1; (with temperature fluctuations < 10 K: Turn down 1:1)
Characteristics deviation		< ± 0,5; (Turn down 1:1; including linearity, hysteresis and repeatability)
	[% of the span]	
Linearity deviation		< ± 0.5 % (limit value setting according to DIN EN IEC 62828-1) Turn down 1:1
	[% of the span]	
Hysteresis deviation		< ± 0,25; (Turn down 1:1)
	[% of the span]	
Long-term stability		< ± 0,1; (Turn down 1:1; per year)
	[% of the span]	



Pressure sensor for pneumatics

PQ-010-RHR18-MFRKG/AS/

Temperature coefficient zero point [% of the span / 10 K]	0,2; (Turn down 1:1)	
Temperature coefficient span [% of the span / 10 K]	0,2; (Turn down 1:1)	
Reaction times		
Response time [ms]	6	
Damping process value dAP [s]	0...4	
Damping for the analog output dAA [s]	0...99.99	
Software / programming		
Parameter setting options	display can be rotated and switched off; analog output selectable and scalable; Teach function; simulation function; Diagnostic function	
Interfaces		
Communication interface	IO-Link	
IO-Link revision	1.1.3	
SDCI standard	IEC 61131-9: 2019-06	
SIO mode	yes	
Required master port class	A	
Process data analog	1	
Process data binary	2	
IO-Link resolution pressure [bar]	0.001	
IO-Link process data (cyclical)	Function	bit length
	pressure	16
	device status	4
	SSC1.1	1
	SSC1.2	1
IO-Link functions (acyclical)	application specific tag; internal temperature; Medium temperature	
Supported DeviceIDs	Type of operation	DeviceID
	default	1717
Operating conditions		
Ambient temperature	0...60 °C	32...140 °F
Storage temperature	-25...85 °C	-13...185 °F
Protection	IP 65	
Tests / approvals		
EMC	DIN EN 61326-1	
Shock resistance	DIN EN 60068-2-27	50 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	20 g (10...2000 Hz)
UL approval	UL approval number	J067
	File number UL	E174189
Pressure equipment directive	sound engineering practice; can be used for stable gases fluid group 2	
Mechanical data		
Weight [g]	53.2	
Housing	rectangular	
Dimensions [mm]	37.7 x 30 x 38.6	
Material	PBT; PC; TPE; NBR; FKM; brass; silicon (coated)	

PQC862



Pressure sensor for pneumatics

PQ-010-RHR18-MFRKG/AS/

Materials (wetted parts)	PBT; FKM; brass; silicon (coated)
Min. pressure cycles	50 million
Process connection	threaded connection G 1/8 Internal thread (2x)

Displays / operating elements		
Display	Display 1"	128 x 96 pixels
	Switching status	1 x LED, yellow
Display unit	bar; MPa; psi; mmHg; inHg; kgf/cm²	

Accessories	
Items supplied	head cap screw: 2 x (M3 x 8 mm)


Remarks	
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M8; coding: A; Contacts: 4, gold-plated



Connection



Electrical connection - plug

1	L+	
2	OUT	AO
3	L-	
4	MP	DO, IO-Link

AO: analog output; DO: digital output; MP: multi-function connection

PQC862



Pressure sensor for pneumatics

PQ-010-RHR18-MFRKG/AS/

Diagrams and graphs

drilling template

