


SL5201



Airflow monitor

SLG23XEE40KG/2M/BS



Product characteristics

Number of inputs and outputs	Number of analog outputs: 1
Process connection	Clamp fitting Ø 23 mm

Application

Special feature	gold-plated contacts
Medium temperature [°C]	35...65
Pressure rating	1 bar 0.1 MPa

Electrical data

Operating voltage tolerance [%]	-10...10
Operating voltage [V]	24 DC
Current consumption [mA]	< 35
Min. insulation resistance [MΩ]	100; (500 V DC)
Power-on delay time [s]	90

Inputs / outputs

Number of inputs and outputs	Number of analog outputs: 1
------------------------------	-----------------------------

Outputs

Total number of outputs	1
Output signal	analog signal
Number of analog outputs	1
Analog voltage output [V]	0...10

Measuring/setting range

Flow range [cm/s]	200...2000
Note on flow range	= 1...10 V

Accuracy / deviations

Max. temperature gradient of [K/min] medium	1
--	---

SL5201



Airflow monitor

SLG23XEE40KG/2M/BS

Operating conditions

Ambient temperature	[°C]	-10...50
Storage temperature	[°C]	-25...85
Max. relative air humidity	[%]	90
Protection		IP 65

Tests / approvals

MTTF	[years]	726
------	---------	-----

Mechanical data

Weight	[g]	219
Housing		tubular
Dimensions	[mm]	Ø 23 / L = 142
Material		housing: PBT; sensor surface: titanium
Materials (wetted parts)		PBT; titanium
Process connection		Clamp fitting Ø 23 mm

Displays / operating elements

Display	Power	LED, green
---------	-------	------------

Accessories

Items supplied	Mounting clamp: 1, E40048
----------------	---------------------------

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Cable: 2 m; 4 x 0.5 mm²

Connector: 1 x M16 (Binder 09-0309-00-04); coding: A; Contacts: gold-plated



Connection

