


TA4115

Temperature transmitter

TA-050CLEM14-A-ZVG/DE



Product characteristics

Number of inputs and outputs	Number of analog outputs: 1	
Measuring range	-50...150 °C	-58...302 °F
Process connection	threaded connection G 1/4 external thread	
Installation length EL [mm]	50	

Application

Measuring element	1 x Pt 1000; (to DIN EN 60751, class A)	
Media	liquids and gases	
Pressure rating [bar]	400	

Electrical data

Operating voltage [V]	10...30 DC; (cULus - Class 2 source required)	
Current consumption [mA]	< 30	
Protection class	III	
Reverse polarity protection	yes	

Inputs / outputs

Number of inputs and outputs	Number of analog outputs: 1	
------------------------------	-----------------------------	--

Outputs

Total number of outputs	1	
Output signal	analog signal	
Number of analog outputs	1	
Analog current output [mA]	4...20	
Max. load [Ω]	(U _b - 8,5 V) / 21,5 mA; 24 V: 720 Ω	
Short-circuit protection	yes	
Overload protection	yes	

Measuring/setting range

Probe length L [mm]	38	
---------------------	----	--

TA4115



Temperature transmitter

TA-050CLEM14-A-ZVG/DE

Measuring range	-50...150 °C	-58...302 °F
-----------------	--------------	--------------

Resolution		
------------	--	--

Resolution of analog output	[K]	0.04
-----------------------------	-----	------

Accuracy / deviations

Precision analog output	[K]	$\pm 0,3 + (\pm 0,1 \% \text{ MS})$
-------------------------	-----	-------------------------------------

Temperature coefficient	0,1; (In case of deviation from the reference condition $25 \pm 5 \text{ °C}$)	
	[% of the span / 10 K]	

Reaction times

Dynamic response T05 / T09	[s]	1 / 3; (according to DIN EN 60751)
----------------------------	-----	------------------------------------

Operating conditions

Ambient temperature	[°C]	-40...100
---------------------	------	-----------

Storage temperature	[°C]	-40...100
---------------------	------	-----------

Protection	IP 68; IP 69K	
------------	---------------	--

Tests / approvals

EMC	DIN EN 61000-6-2	
-----	------------------	--

	DIN EN 61000-6-3	
--	------------------	--

Shock resistance	DIN EN 60068-2-27	50 g (11 ms)
------------------	-------------------	--------------

Vibration resistance	DIN EN 60068-2-6	20 g (10...2000 Hz)
----------------------	------------------	---------------------

MTTF	[years]	1092
------	---------	------

UL approval	UL approval number	K006
-------------	--------------------	------

Mechanical data

Weight	[g]	97.5
--------	-----	------

Housing	tubular	
---------	---------	--

Dimensions	[mm]	$\varnothing 21 / L = 109.6$
------------	------	------------------------------

Material	stainless steel (1.4404 / 316L); PPS; FKM	
----------	---	--

Materials (wetted parts)	stainless steel (1.4404 / 316L); FKM	
--------------------------	--------------------------------------	--

Process connection	threaded connection G 1/4 external thread	
--------------------	---	--

Probe diameter	[mm]	6
----------------	------	---

Installation length EL	[mm]	50
------------------------	------	----

Remarks

Remarks	The values for accuracy apply to flowing water.	
---------	---	--


	referring to UL: for use on a low voltage circuit with overcurrent protection	
--	---	--

	in accordance with UL873 tab. 28.1 or $I_{\text{max}} = 100/U_b$ (U_b = voltage of the circuit)	
--	--	--

Pack quantity	1 pcs.	
---------------	--------	--

Electrical connection

Connector: 1 x DEUTSCH connector (DT04-3P); Contacts: 3




TA4115

Temperature transmitter

TA-050CLEM14-A-ZVG/DE



Connection



OUT: analog output