



ISO calibration certificate for flow sensors

ISO-Kalibrierung SD

Werkskalibrierschein
Factory calibration certificate

Messumformer-Typ: SD6xx
transmitter type: SD6xx
Serien-Nr.: 123456789
serial no.: 123456789
Messbereich: 0...100 l/min
temperature range: 0...100 l/min
Ausgangssignal: 4...20 mA
output: 4...20 mA
Genauigkeit: ±0.5%
accuracy: ±0.5%
Kalibrierdatum: 12.12.2017
date of calibration: 12.12.2017

Auftragsnummer: 123456789
job no.: 123456789
Referenzgerät: 123456789
reference unit: 123456789
Prüfnormal, Temperatur: 123456789
testing device, temperature: 123456789
Serien-Nr.: 123456789
serial no.: 123456789
PTB-Zertifikat: 123456789
PTB certificate: 123456789
Umgebungstemperatur: 123456789
ambient temperature: 123456789

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The accuracy of the measurement is guaranteed by the use of calibrated measuring devices and the use of the appropriate measuring method. The accuracy of the measurement is guaranteed by the use of calibrated measuring devices and the use of the appropriate measuring method. The accuracy of the measurement is guaranteed by the use of calibrated measuring devices and the use of the appropriate measuring method.

The present certificate is valid for the duration of the measurement and the use of the sensor. The present certificate is valid for the duration of the measurement and the use of the sensor. The present certificate is valid for the duration of the measurement and the use of the sensor.

The present certificate is valid for the duration of the measurement and the use of the sensor. The present certificate is valid for the duration of the measurement and the use of the sensor. The present certificate is valid for the duration of the measurement and the use of the sensor.

Mechanical data	
Weight	[g] 15
Remarks	
Remarks	the ISO calibration certificate is not recognized according to the EA MLA (Multilateral Agreement) and is therefore considered as not traced. The calibration certificate must be ordered in conjunction with a sensor. The corresponding sensor is delivered along with the calibration certificate. The calibration certificate is in two languages (German/English). Subsequent orders are only possible if the sensor is in a clean condition upon return. In the internet version of the data sheet a sample certificate is stored in the tab "Downloads". for the SDx6xx sensors, the issue is only possible for the air characteristics
Pack quantity	1 pcs.